1. (canceled)

2. (canceled)

5

3. (canceled)

4. (canceled)

10   5. (canceled)

6. (canceled)

7. (canceled)

15

8. (canceled)

9. (canceled)

20   10. (canceled)

11. (canceled)

12. (canceled)

25

13. (canceled)

14. (currently amended) An integrated circuit constructed on one chip,

the integrated circuit comprising:

30   a plurality of data stream inputs and/or outputs that receive and/or transmit streams of

data;

        a plurality of data stream processors that process the streams of data, each data stream

processor being coupled to a data stream input and/or data stream output and each data

stream processor processing a stream of data from the data stream input and/or output the

3

data stream processor is coupled to as the data stream is received from the data stream input
and/or transmitted to the data stream output,

each data stream processor including

a writeable instruction memory containing instructions and

5   a control data processor that controls the data stream processor by sequentially executing
instructions from the writeable instruction memory; and

the integrated circuit further comprising

an aggregator that aggregates certain of the data stream processors so that the
aggregated data stream processors cooperate in processing a stream of data; and

10   a context processor that responds to information received from a given data stream
processor that is processing a data stream to produce information about the given data
stream's context and provide the context information to the given data stream processor;
the given data stream processor using the context information to process the data stream
and the integrated circuit being constructed on one chip.

15

15. (previously presented) The integrated circuit set forth in claim 14 wherein:

the control data processor is a general-purpose microprocessor that has an industry-
standard architecture, whereby programs for the control data processor may be developed
20   using standard tools for the architecture.

16. (previously presented) The integrated circuit set forth in claim 14 wherein:

the streams of data include a serial stream and a parallel stream.

25

17. (currently amended) The integrated circuit set forth in claim 14 wherein the ~~integrated
circuit further~~aggregator comprises:

~~an aggregator that aggregates certain of the data stream processors so that the
30   aggregated data stream processors cooperate in processing a stream of data, the aggregator
including~~

configurable interconnections between the aggregated data stream processors;

a configurable operation coordinator that coordinates operation of the aggregated data
stream processors; and

4

a writeable configurator that specifies the configurable interconnections and the configurable operation coordinator as required to aggregate the data stream processors.

5   18. (previously presented) The integrated circuit set forth in claim 14 wherein:

a data stream input and/or output includes a plurality of I/O pins that receive and/or transmit signals and

the integrated circuit further comprises:

a writeable configuration specifier for specifying a configuration of a data stream

10   input and/or output; and

configuration circuitry coupled between the plurality of I/O pins and the data stream processor and responsive to the configuration specifier for configuring the data stream input and/or output as specified by the configuration specifier, whereby the integrated circuit may be used with a plurality of transmission protocols.

15

19. (previously presented)   The integrated circuit set forth in claim 14 wherein each data stream processor further comprises:

a receive processor that operates under control of the control data processor to process

20   the data stream received from the data stream input and/or

a transmit processor that operates under control of the control data processor to process the data stream for output to the data stream output.

25   20. (previously presented) The integrated circuit set forth in claim 19 wherein each of the receive processor or the transmit processor further comprises:

a writeable instruction memory containing instructions; and

the receive processor or the transmit processor sequentially executes certain of the instructions to process the data stream.

30

21. (previously presented) The integrated circuit set forth in claim 19 wherein:

the receive processor and/or the transmit processor have a plurality of processing components and are configurable to bypass one or more of the components in processing the

data streams.

22. (canceled)

5

23. (previously presented) The integrated circuit set forth in any one of claims 14 through 21
wherein:

a stream of data contains control data and payload;

10   a received stream of data is processed in a receiving data stream processor to extract
the control data and the payload and a transmitted stream of data is processed in a
transmitting data stream processor to add control data to the payload; and

the integrated circuit further comprises

a buffer manager coupled to the data stream processors that provides addresses of

15   buffers for storing payload and responds to a write operation with a buffer address to write
payload to the addressed buffer and to a read operation with a buffer address to read payload
from the addressed buffer; and

a queue manager coupled to the data stream processors that manages queues of
descriptors of payload, each descriptor including at least a buffer address, the queue manager

20   responding to an enqueue command by enqueuing a descriptor provided with the command to
a queue specified in the command and responding to a dequeue command by dequeuing a
descriptor from the queue specified in the command,

a data stream processor responding to a received stream of data by performing a write
operation to the buffer manager with the received data stream's payload and an address

25   provided by the buffer manager and performing an enqueue operation with a descriptor
containing the address and transmitting a stream of data by performing a dequeue operation,
using the address in a descriptor obtained as a result of the dequeue operation in a read
operation to the buffer manager, producing a data stream using the payload received from the
buffer manager, and transmitting the produced data stream.